102004052439.4 2004P16587WOUS

IAP20 Rec'd PCT/PTO 08 FEB 2006

WRITTEN REPORT
OF THE INTERNATIONAL
SEARCHING AUTHORITY (ANNEX)

International Application No. PCT/EP2005/054884

On Point V

1. Reference is made to the following document:

D: DE 101 38 838 A1

2. Document D is regarded as the closest prior art.

It discloses (the references in brackets relate to this document):

A fuel pump (5) having a driven impeller (8) facing a casing part, with guide vane rings arranged in the impeller (8) concentrically enclosing one another and defining blade chambers (9-11), with partially annular fuel feed ducts (15-17) facing the guide vane rings in the casing part, and with outlet ducts (13-14) connected to the partially annular ducts (15-17), the rings of blade chambers (9-11) and the partially annular ducts (15-17) forming a radially inner delivery chamber (19) and a radially outer delivery chamber (18).

(see column 2, paragraph 19 - column 3, paragraph 20; Fig. 1)

- 1 -

from which the subject matter of the independent claim 1 differs in that the radially outer delivery chamber (17) is connected to the radially inner delivery chamber (16) via a connecting duct (29).

The subject matter of claim 1 is therefore new (article 33 (2) of the PCT).

The object of the present invention is therefore to ensure that the fuel pump guarantees a sufficiently high delivery capacity of the inner delivery chamber (16) even at a low speed.

This object is achieved in that the pressure differentials between the radially outer delivery chamber (17) and the radially inner delivery chamber (16) are compensated for by a connecting duct (29).

Such a solution is not proposed by the prior art disclosed. It is therefore based on an inventive step (article 33(3) of the PCT).

WRITTEN REPORT
OF THE INTERNATIONAL
SEARCHING AUTHORITY (ANNEX)

International Application No. PCT/EP2005/054884

Claims 2-13 are dependent on claim 1 and thereby also fulfill the requirements of the PCT with regard to novelty and inventive step.